

DATA SHEET

- The PP-8444A/U Universal Portable Battery Charger is a “State of the Art” high performance lightweight portable unit designed for field deployment or use in a shop environment . The charger’s main purpose is to provide fast reactivation of various types of rechargeable batteries. Each of the battery types capable of being charged are connected to the charger using the appropriate battery adapter (plate or cable) which then can fast charge (2) similar batteries in two hours. The charger comes equipped with (4) cord posts as shown, used for the wrap-around storage

Description	Universal Battery Charger, with multi-voltage input for world wide usage
National Stock Number	6130-01-495-2389
For Use with	C ⁴ I series of Rechargeable Batteries and Adapters
Power Requirements	85 to 132V, 170 to 265V AC, (47 to 63 Hz), or 24V DC
Nominal Dimensions	Length: 13.250” (336.55mm) Width: 10.500” (266.70mm) Height: 7.00” (177.80mm)
A/C Cable Length	5.0 Ft. (1.52mm) Long, 3 wire power cord
Optional	DC input cord (Nato Slave Type) 11.5 Ft. long (3.5m)
Nominal Weight	11 Lbs. (5.0 Kg)
Case Material & Color	Hi-Impact ABS, Olive Drab #34088

WHEN ORDERING SPECIFY P/N:
BTC-70801

PACKAGING

UNIT BOX
1 per

MASTER CARTON
1 Ea.

Weight: 12 Lbs. (5.45 Kg)
Cubes: .77 Ft³ (.021 m³)

